

WEBSIDE DIRECTION

GEARSIDE



PRODUCT VIEW DIE VIEW DIE VIEW
 CUSTOMER: PO# 33905Q
 SALES: JV ACROSS 1 AROUND 1 REVISION: 0
 TOOTH: 73 PITCH: 1/8
 DATE: 3-9-2005
 DRW.BY: IR


← WEB DIRECTION →

GEAR SIDE

R 165.1866

0000.6

6.0523

Stabilized • Chlorinating Granules

EMERGENCY HANDLING: In case of contamination or decomposition do not reseal container. If possible, isolate container in open and well-ventilated area. Flood with large volumes of water. Dispose of contaminated material in an approved landfill area.

PRECAUTIONARY STATEMENTS:

HAZARDS TO HUMANS AND DOMESTIC ANIMALS.

DANGER: Corrosive. Causes irreversible eye damage. May be fatal if inhaled. Harmful if swallowed or absorbed through skin. Do not get in eyes, on skin, or on clothing. Do not breathe dust, vapor or spray mist. Wear goggles, face shield or safety glasses. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. Remove and wash contaminated clothing before reuse.

CHEMICAL HAZARDS. DANGER: Strong oxidizing agent. Use only clean, dry utensils. Mix only into water. Contamination with moisture, dirt, organic matter, or other chemicals (including other pool chemicals) or other foreign matter may start a chemical reaction with generation of heat, liberation of hazardous gases, and possible generation of fire and explosion. Avoid any contact with flaming or burning material, such as a lighted cigarette. Do not use this product in any chlorinating device which has been used with any inorganic or unstabilized chlorinating compounds (e.g. calcium hypochlorite). Such use may cause fire or explosion.

ENVIRONMENTAL HAZARD: This pesticide is toxic to fish and aquatic organisms.

STORAGE AND DISPOSAL:

Storage: Keep product dry in a tightly closed container when not in use. Store in a cool, dry, well-ventilated area away from heat or open flames. Do not reuse or refill empty container.

Disposal: If empty: Nonrefillable container. Do not reuse or refill this container. Place in trash or offer for recycling, if available. If partially filled: Call your local solid waste agency or 1-800-CLEANUP (1-800-253-2687) for disposal instructions. Never place unused product down any indoor or outdoor drain.

DIRECTIONS FOR USE: It is a violation of federal law to use this product in a manner inconsistent with its labeling. This product is designed to dissolve quickly and completely providing a steady source of available chlorine in swimming pools to control the growth of algae, kill bacteria and destroy organic contaminants.

READ THE PRECAUTIONARY STATEMENTS BEFORE USE:

METHOD OF APPLICATION: Broadcast the product evenly over a wide area in the deepest part of the pool with water circulating.

ROUTINE CHLORINATION: Throughout the pool season, adjust pH to 7.2-7.6 with Blue Wave pH Increaser or Blue Wave pH Reducer. Follow label directions. Broadcast 3 oz. of this product per 10,000 gallons pool water every other day or as often as needed to maintain chlorine residual at 2-4 ppm. This quantity may vary depending on bather load, temperature and other conditions. Re-entry into treated pools is prohibited above levels of 3 ppm chlorine. As a pre-

ventative treatment, you should shock treat weekly to prevent pool problems which may occur when bathing loads are high, water appears hazy or dull, unpleasant odors or eye irritation occur, after heavy wind and rainstorms, when temperatures are high, in case of colored water, or if algae develops with resulting green color and slimy feeling.

SHOCK TREATMENT: Adjust pH to 7.2 to 7.4 with a pH increaser or pH decreaser. Follow label directions. Shock treat weekly to kill bacteria, control algae and organic material. As an alternative, add 18 oz. of this product per 10,000 gallons of pool water.

WATER BALANCE: To provide optimum product performance, swimmer comfort and crystal clear water, always maintain pH in the 7.2-7.8 range, total alkalinity in the 90-125 parts per million (ppm) range and calcium hardness above 200 ppm. Use a reliable test kit that measures all these ranges. Make necessary adjustments with the appropriate pool care products.

SPA AND HOT TUB USE: Each level teaspoon (0.17 ounces) of this product will provide approximately 1.4 ppm available chlorine in 500 gallons of water. Using an appropriate test kit, test and adjust the water to the following values: pH 7.2-7.8, total alkalinity 60-100 ppm, calcium hardness 200 ppm minimum. Maintain these conditions for proper spa and hot tub operation by frequent testing with a test kit. Do not allow cyanuric acid level to exceed 150 ppm. It is recommended that spas and hot tubs be drained every 30-90 days. More often under heavy use. Consult manufacturer's recommendations concerning the compatibility of chlorine sanitizers with their equipment. Some oils, lotions, fragrances and cleaners may cause foaming or cloudy water and may react with chlorine sanitizers to reduce their efficacy.

START-UP (FRESHLY FILLED)

1. Turn on the circulation system and ensure that it is operating properly.
 2. Add 6 teaspoons of this product for each 500 gallons of water.
- Check the free available chlorine (FAC) and, if below 4-5 ppm, repeat as needed. Re-entry into treated spas is prohibited above levels of 3 ppm of chlorine.

REGULAR USE:

Turn on the circulation system and ensure that it is operating properly. Scatter approximately 3 teaspoons per 500 gallons of this product over the surface of water. Always use a clean dry spoon. Test for FAC and add additional product, if necessary, to attain 4-5 ppm FAC. Maintain 1-3 ppm FAC while the spa or hot tub is in use. After each use, shock treat with 9 teaspoons per 500 gallons water to control odors and algae. Repeat as needed. Re-entry into treated spas is prohibited above levels of 3 ppm of chlorine.

Distributed by:
Blue Wave Products
 St. Charles, IL 60174
1-800-759-0977

EPA REG. 46043-11-63084
EPA Est. No. 46043-FL-1

PRODUCT VIEW PO# ADT # 33905Q
 CUSTOMER: DIE # TOOTH: 73 PITCH: 1/8
 SALES: JV ACROSS 1 DATE: 3-9-2005
 american die technology AROUND 1 REVISION: 0 DRW.BY: IR

