

### PRECAUTIONARY STATEMENTS

CAUTION. Contains calcium chloride. IRRITANT TO EYES AND SKIN. HARMFUL IF SWALLOWED. Avoid contact with eyes, skin, and clothing. Avoid breathing dust and use adequate ventilation. Wear goggles and use rubber gloves when handling. Wash thoroughly after handling.

### DIRECTIONS FOR USE

1. Measure spa water for hardness (calcium level) using a suitable test kit
2. As a general rule, 3-4 ounces of Hardness Increaser per 500 gallons of spa water will raise the hardness (calcium) level by 50 ppm. For plaster spas, ideal hardness levels should be maintained between 225 - 300 ppm. For vinyl, fiberglass, and non-masonry spas, ideal hardness levels should be maintained between 175 - 225 ppm.
3. Add hardness increaser directly to the spa water by scattering over a large area. Make certain that the circulation equipment (filter pump) is operating. DO NOT PRE-DISSOLVE IN A BUCKET OR ADD TO A SMALL QUANTITY OF WATER. Heat is generated when this product is dissolved in water.

NOTE: If spa up or alkalinity increaser has recently been added to spa water (within 24 hours), it is best not to add this product until the next day. An insoluble precipitate is likely to form resulting in cloudy spa water. GENERAL INFORMATION: Low calcium hardness in your spa can result in staining, etching or distortion of the spa's surface. Plaster damaged by low calcium hardness can become abrasive and uncomfortable to spa users. Rough plaster can also increase algae problems, thus causing greater difficulty in keeping the plaster surface clean. This can be prevented by using hardness increaser. The calcium hardness level should be maintained in the range of 225 - 300 ppm for plaster spas (175 - 225 for vinyl, fiberglass, and non-masonry spas). DO NOT allow the calcium hardness level to fall below 200 ppm for plaster spas.

PRACTICAL TREATMENT: Contains calcium chloride. IRRITANT. HARMFUL IF SWALLOWED. Avoid contact with eyes, skin, and clothing. IN CAST OF CONTACT WITH SKIN: Brush off excess chemical and flush skin with water for 15 minutes. Remove contaminated clothing and shoes. Call physician if irritation persists. Clean clothing and shoes before reuse. IN CASE OF CONTACT WITH EYES: Flush eyes immediately with water for 15 minutes with large quantities of water. Call a physician. IF SWALLOWED: DO NOT INDUCE VOMITING. Drink a large quantity of water. Never give anything by mouth to an unconscious person. CALL A PHYSICIAN. IF INHALED: Remove to fresh air. Provide oxygen if necessary. If breathing difficulties persist, call a physician.

STORAGE AND DISPOSAL: Store closed container in a cool, dry, and well-ventilated space. When container is empty, rinse thoroughly with water, wrap securely in newspaper, and place in trash collection.



# hardness increaser

# SS

- Maintains proper calcium levels



Distributed By:  
BLUE WAVE PRODUCTS INC. BW ITEM# P113  
1745 Wallace Ave. St. Charles, IL 60174

NET WT. 1 lb. (454g)

**CAUTION**  
KEEP OUT OF REACH OF CHILDREN

See back panel for practical treatment and precautionary statement.